

Tuneable Laser Source

F
T
E
6
0
0
0

Features:

- Selectable Step Size Down to 50 GHz
- Selectable Start & Stop Channels
- Settable in Wavelength or Frequency
- Settable Dwell Time
- Available in C or L Band
- Sealed Rugged Case with Impact Resistant Boot
- USB PC Interface with Remote operation Capability
- Battery Operated or International Line Voltage
- Simple Operation with On-Line Help Mode
- Lowest Cost Hand Held Tuneable Laser Source
- Interchangeable Fiber Optic Connectors
- Up to 88 Channels on the ITU Grid
- Fast Turn-On
- 4" Color Display
- 4 hr Battery Life



The Terahertz Technologies FTE-6000 Hand Held Tuneable Laser Source (TLS) is available in C and L Bands. The FTE-6000 is manufactured in our rugged splash proof housing with a highly protective boot. Our TLS displays in wavelength, frequency or ITU channel. The Tuneable Laser Source is a great match with our FTE-8000 (Optical Spectrum Analyzer) for installation, commissioning and trouble shooting of DWDM networks. The FTE-6000 offers a fast start up with minimal warm up required and provides very stable wavelength and power outputs. As with all of our Advanced tests equipment series, the FTE-6000 is affordable, easy to use and rugged. Ask about our kit offerings, such as the FTE-8600 Combo Kit.

Terahertz
TTInc. 




Made In the USA

Terahertz Technologies Inc.
169 Clear Rd, Oriskany NY 13424
Phone: 315-736-3642 Fax: 315-736-4078
email: sales@terahertztechnologies.com
web: www.terahertztechnologies.com

©09/11 Terahertz Technologies Inc.

Ideal for Installation, Maintenance and Upgrades of DWDM Systems



With the TTI FTE-6000 Tuneable Light Source, you can conduct a sweep of the ITU Grid by setting your beginning and ending wavelengths. You can also set step size, power level, dwell time and whether the sweep should move up or down the scale. It may also be set to conduct continuous sweeps.

Laser Safety

Class 1M Laser Product



Specifications

Frequency Range	FTE-6000 C 192 - 196 THz (1529-1563nm) FTE-6000 L 187 - 191 THz (1569-1607nm)
Accuracy	1.5 GHz
Line Width	1 MHz
Side Mode Suppression Ration	45 dB
Output Power Range	+3 dBm + 9 dBm
Power Setting Resolution	0.01 dB
Power Variation over Wavelength Range	+0.0 to -0.5 dB
Minimum Channel Spacing	50 GHz (0.4nm)
Fiber Type	9/125 μ m
Relative Intensity Noise	-140 dB/Hz
Graphical Display	4 in Color TFT
Dimensions	7.75 x 4.5 x 2.25 inches
Weight	2 lbs
Battery	Rechargeable NiMH - 4 hours operating time
Power	100-240 universal US, GB, EU, AU Mains
Environmental	Operation -10°C to + 40°C
Accessories Included	Universal power supply with mains for US, UK, CE and AU. Interchangeable FC and SC adaptors, Windows TM Compatible Software, USB Cable, Manual and Rubber Boot

TTI reserves the right to change specifications without notice.

Part Numbers

FTE-6000C	C-Band Tuneable Laser Source
FTE-6000L	L-Band Tuneable Laser Source
FTE-8600C	C-Band Tuneable Laser Source with C Band Optical Spectrum Analyzer
FTE-8600L	L-Band Tuneable Laser Source with L Band Optical Spectrum Analyzer



Made In the USA

Terahertz Technologies Inc.
169 Clear Rd, Oriskany NY 13424
Phone: 315-736-3642 Fax: 315-736-4078
email: sales@terahertztechnologies.com
web: www.terahertztechnologies.com

TTI makes every effort to insure all statements and information for the products referred to in this document are accurate and reliable. TTI can not accept any responsibility for errors, omissions or miss statements, nor can they accept responsibility for any actions taken based on the information demonstrated herein. TTI reserves the right to make changes of any kind to the product referred to in this document without prior notice.
© 09/2011 Terahertz Technologies Inc.